

Measurement printout

Car standard measurement

Beissbarth © * ML 8 Easy

M * R- ** OK * USER // 112 / C

Date: 05.10.2017 11:29:02



Version (program)
v5.0b3101/v5.0b3101

Version (CCD)
v5.0b3101

Version (target data)
USER

Serial number
C10000942

Last service
27.12.2016

VANTAGE AUTOMOTIVES LIMITED
305 ALEXANDRA ROAD
SINGAPORE

Customer

Vehicle

Registration: SDA 916 E

Order

Vehicle:

USER

PEUGEOT * 308 * Commercial vehicle

Rear Axle		Initial Measurement	Target Data
Camber	left	-1°17'	-0°30' [-1°42'] +0°30'
	right	-0°19'	
Cross Camber		-0°58'	-0°20' [+0°00'] +0°20'
Individual Toe	left	+0°28'	-0°04' [+0°32'] +0°05'
	right	+3°07'	
Total Toe		+3°35'	-0°09' [+1°04'] +0°09'
Setback		-1°41'	
Geometrical driving axis		+1°20'	
Front Axle		Initial Measurement	Target Data
Castor 20°	left	+3°20'	-0°30' [+5°42'] +0°30'
	right	+4°15'	
K.P.I. 20°	left	+1°10'	-0°24' [+12°54'] +0°36'
	right	+1°00'	
Toe out on turns	left	-1°31'	
	right	-1°07'	
Camber	left	-0°28'	-0°36' [-0°18'] +0°24'
	right	-0°59'	
Cross Camber		+0°31'	-0°28' [+0°12'] +0°28'
Individual Toe	left	+0°36'	-0°04' [+0°11'] +0°05'
	right	-0°53'	
Total Toe		-0°16'	-0°09' [+0°21'] +0°09'
Setback		-1°22'	
Included Angle 20°	left	+0°42'	
	right	+0°02'	