

Work Order: R001129
 License: smm3307z
 Technician: fensan 119
 Mileage: 85667
 Date: 13.8.20 14:13

Before

KIA CERATO 1.6 2019

Front : Left

Actual	Before	Specified Range
0°04'	0°05'	-0°53' 0°07'
4°22'	4°22'	4°00' 5°00'
0°03'	-0°06'*	-0°03' 0°09'
11°48'*	11°47'*	13°30' 14°30'
11°52'*	11°52'*	12°37' 14°37'

Camber
 Caster
 Toe
 SAI
 Included Angle
 Turning Angle Diff.

Front : Right

Actual	Before	Specified Range
-0°56'*	-0°57'*	-0°53' 0°07'
5°16'*	5°16'*	4°00' 5°00'
0°03'	0°03'	-0°03' 0°09'
14°10'	14°11'	13°30' 14°30'
13°14'	13°14'	12°37' 14°37'

Front

Cross Camber
 Cross Caster
 Cross SAI
 Total Toe
 Cross Turn Diff.

Actual	Before	Specified Range
1°00'	1°02'	
-0°54'	-0°54'	
-2°22'	-2°24'	
0°06'	-0°02'	-0°06' 0°18'

Rear : Left

Actual	Before	Specified Range
-0°38'*	-0°37'*	-1°42' -0°42'
0°06'	0°06'	-0°02' 0°16'

Camber
 Toe

Rear : Right

Actual	Before	Specified Range
-2°02'*	-2°03'*	-1°42' -0°42'
0°06'	0°05'	-0°02' 0°16'

Rear

Cross Camber
 Total Toe
 Thrust Angle

Actual	Before	Specified Range
1°24'	1°26'	
0°12'	0°11'	-0°04' 0°32'
0°00'	0°00'	

* This value is not within specification. Tire wear, handling and safety problems may result.

Work Order: R001131
 License: smm3307z
 Technician: fensan 810119
 Mileage: 85668
 Date: 14.8.20 18:10



KIA CERATO 1.6 2019

Front : Left

Actual	Before	Specified Range
-0°14'	-0°13'	-0°53' 0°07'
4°16'	4°16'	4°00' 5°00'
0°05'	0°05'	-0°03' 0°09'
13°03'*	13°03'*	13°30' 14°30'
12°50'	12°50'	12°37' 14°37'

Camber
 Caster
 Toe
 SAI
 Included Angle
 Turning Angle Diff.

Front : Right

Actual	Before	Specified Range
-0°39'	-0°39'	-0°53' 0°07'
5°08'*	5°08'*	4°00' 5°00'
0°04'	0°04'	-0°03' 0°09'
13°58'	13°58'	13°30' 14°30'
13°19'	13°19'	12°37' 14°37'

Front

Cross Camber
 Cross Caster
 Cross SAI
 Total Toe
 Cross Turn Diff.

Actual	Before	Specified Range
0°25'	0°26'	
-0°52'	-0°52'	
-0°55'	-0°56'	
0°09'	0°09'	-0°06' 0°18'

Rear : Left

Actual	Before	Specified Range
-0°57'	-0°57'	-1°42' -0°42'
0°05'	0°05'	-0°02' 0°16'

Camber
 Toe

Rear : Right

Actual	Before	Specified Range
-1°41'	-1°41'	-1°42' -0°42'
0°08'	0°08'	-0°02' 0°16'

Rear

Cross Camber
 Total Toe
 Thrust Angle

Actual	Before	Specified Range
0°44'	0°44'	
0°13'	0°13'	-0°04' 0°32'
-0°02'	-0°02'	

* This value is not within specification. Tire wear, handling and safety problems may result.