























COMPUTERISED 4 WHEEL ALIGNMENT HUNTER DSP700

Company:

PRECISE AUTO SERVICE

VIN:

SKD 4573 K

Date

22.10.20 13:33

SKD 4573 K

Mercedes-Benz : 204 (C Class 2007-15) : without 4MATIC : Sedan/Wagon Standard Suspension Europe version/USA : 02/2008-

Front: Left

Actual	Before	Specified Range
-0°33'	-0°33'	-0°48' -0°05'
10°46'	10°46'	0 40 -0 08
0°08'	0°07'	0°00' 0°10'
18°55'	18°55'	0 00 0 10
18°22'	18°22'	
		-2°12' -1°12'

Camber
Caster
Toe
SAI
Included Angle
Turning Angle Diff.

Front : Right		
Actual	Before	Specified Range
-0°14'	-0°14'	-0°48' -0°05'
10°58'	10°58'	
0°09'	0°09'	0°00' 0°10'
7°53'	7°53'	构计
7°39'	7°39'	7
100		-2°12' -1°12'

Front

Cross Camber Cross Caster Cross SAI Total Toe Cross Turn Diff.

Actual	Before	Specified Range
-0°18'	-0°19'	-0°24' 0°24'
-0°11'	-0°11'	-0°30' 0°30'
11°02'	11°02'	
0°17'	0°17'	0°00' 0°20'
	0 17	0 00 0 20

Rear: Left

Actual	Before	Specified Range
0°59'	-0°59'	-1°34' -0°34'
0°05'	0°05'	0°05' 0°19'

Camber Toe

Rear : Right		
Actual	Before	Specified Range
-1°24'	-1°24'	-1°34' -0°34'
0°17'	0°17'	0°05' 0°19'

Rear

Cross Camber Total Toe Thrust Angle

Actual	Before	Specified Range
0°24'	0°25'	-0°30' 0°30'
0°22'	0°22'	0°17' 0°31'
-0°06'	-0°06'	-0°15' 0°15'

COMPUTERISED 4 WHEEL ALIGNMENT HUNTER DSP700

Company:

PRECISE AUTO SERVICE

/IN:

SKD 4573 K

Date

20.10.20 13:17



SKD 4573 K

Wercedes-Benz : 204 (C Class 2007-15) : without 4MATIC : Sedan/Wagon Standard Suspension Europe version/USA : 02/2008-

Front : Left

Actual	Before	Specified Range
-1°57'	-1°57'	-0°48' -0°05'
10°48'	10°48'	7 10 0 00
0°15'	0°15'	0°00' 0°10'
24°07'	24°07'	7 00 0 10
22°10'	22°10'	
*		-2°12' -1°12'

Camber
Caster
Toe
SAI
Included Angle
Turning Angle Diff.

Front: Right Actual Before Specified Range -0°10' -0°10' -0°48' -0°05' 10°50' 10°50' 0°15' 0°15' 0°00' 0°10' 11°44' 11°44' 11°34' 11°34' -2°12' -1°12'

Front

Cross Camber Cross Caster Cross SAI Total Toe Cross Turn Diff.

Actual	Before	Specified Range
-1°46'	-1°46'	-0°24' 0°24'
-0°01′	-0°01'	-0°30' 0°30'
12°23'	12°23'	
0,30,	0°30'	0°00' 0°20'

Rear: Left

Actual	Before	Specified Range
·1°06'	-1°06'	-1°34' -0°34'
0°18'	0°18'	0°05' 0°19'

Camber Toe

Actual	Before	Specified Range
-1°23'	-1°23'	-1°34' -0°34'
0°11'	0°11'	0°05' 0°19'

Rear: Right

Rear

Cross Camber Total Toe Thrust Angle

Actual	Before	Specified Range
0°17'	0°17'	-0°30' 0°30'
0°29'	0°29'	0°17' 0°31'
0°03'	0°03'	-0°15' 0°15'