

Work Order: R044066
VIN: SLE5422P
Year: 14
Date: 14.4.21 11:58



SLE5422P

Mazda : Mazda5 : 2011-18 (CW) : Rest of World : Standard Suspension

Front : Left

Actual	Before	Specified Range
-2°52'	-2°52'	-1°42' 0°18'
3°14'	3°14'	2°15' 4°15'
-0°24'	-0°24'	-0°06' 0°17'
14°53'	14°53'	
12°01'	12°01'	

Camber
Caster
Toe
SAI
Included Angle
Turning Angle Diff.

Front : Right

Actual	Before	Specified Range
-0°37'	-0°37'	-1°42' 0°18'
3°04'	3°04'	2°15' 4°15'
-0°03'	-0°03'	-0°06' 0°17'
10°36'	10°36'	
9°59'	9°59'	

Front

Cross Camber
Cross Caster
Cross SAI
Total Toe
Cross Turn Diff.

Actual	Before	Specified Range
-2°15'	-2°16'	-1°30' 1°30'
0°10'	0°10'	-1°30' 1°30'
4°17'	4°17'	
-0°27'	-0°27'	-0°11' 0°33'

Rear : Left

Actual	Before	Specified Range
-1°55'	-1°55'	-2°26' -0°26'
0°08'	0°08'	-0°03' 0°19'

Camber
Toe

Rear : Right

Actual	Before	Specified Range
-1°54'	-1°55'	-2°26' -0°26'
-0°03'	-0°02'	-0°03' 0°19'

Rear

Cross Camber
Total Toe
Thrust Angle

Actual	Before	Specified Range
-0°01'	0°00'	-1°30' 1°30'
0°05'	0°05'	-0°06' 0°38'
0°05'	0°05'	-0°48' 0°48'