

R019776
22.3.22 9:35
SMP2948P
160-0517



Honda : Stream
4-Wheel Total Alignment

Front : Left

Actual	Before	Specified Range
-0°33'	-0°33'	-0°45' 0°45'
3°48'	3°48'	3°15' 5°15'
-0°04'	-0°04'	-0°05' 0°05'
11°19'	11°19'	9°55' 11°55'
10°46'	10°46'	9°10' 12°40'

Camber
Caster
Toe
SAI
Included Angle
Turning Angle Diff.

Front : Right

Actual	Before	Specified Range
-1°57'	-1°57'	-0°45' 0°45'
3°55'	3°55'	3°15' 5°15'
-0°24'	-0°24'	-0°05' 0°05'
12°42'	12°41'	9°55' 11°55'
10°44'	10°44'	9°10' 12°40'

Front

Cross Camber
Cross Caster
Cross SAI
Total Toe
Cross Turn Diff.

Actual	Before	Specified Range
1°24'	1°24'	-0°45' 0°45'
-0°08'	-0°08'	
-1°23'	-1°23'	
-0°28'	-0°28'	-0°11' 0°11'

Rear : Left

Actual	Before	Specified Range
-1°21'	-1°21'	-2°00' 0°00'
0°08'	0°08'	0°03' 0°11'

Camber
Toe

Rear : Right

Actual	Before	Specified Range
-0°51'	-0°51'	-2°00' 0°00'
0°12'	0°12'	0°03' 0°11'

Rear

Cross Camber
Total Toe
Thrust Angle
Axle Offset

Actual	Before	Specified Range
-0°30'	-0°30'	
0°20'	0°20'	0°05' 0°21'
-0°02'	-0°02'	
0mm	0mm	