



Factory Japan 2022.0.1 : Honda : Stream : RN6 : except 17" Wheel  
 4-Wheel Total Alignment

Front : Left

Actual	Before	Specified Range
-1°00'	-1°22'	-0°45' 0°45'
4°33'	4°33'	3°15' 5°15'
0°01'	-0°03'	-0°05' 0°05'
11°40'	12°02'	9°55' 11°55'
10°40'	10°40'	9°10' 12°40'

Camber  
 Caster  
 Toe  
 SAI  
 Included Angle  
 Turning Angle Diff.

Front : Right

Actual	Before	Specified Range
-0°43'	-0°27'	-0°45' 0°45'
4°12'	4°12'	3°15' 5°15'
0°04'	-0°02'	-0°05' 0°05'
11°10'	10°53'	9°55' 11°55'
10°27'	10°27'	9°10' 12°40'

Front

Cross Camber  
 Cross Caster  
 Cross SAI  
 Total Toe  
 Cross Turn Diff.

Actual	Before	Specified Range
-0°17'	-0°55'	-0°45' 0°45'
0°20'	0°20'	
0°30'	1°09'	
0°04'	-0°05'	-0°11' 0°11'

Rear : Left

Actual	Before	Specified Range
-1°47'	-2°15'	-2°00' 0°00'
0°05'	-0°25'	0°03' 0°11'

Camber  
 Toe

Rear : Right

Actual	Before	Specified Range
-1°47'	-1°28'	-2°00' 0°00'
0°04'	-0°02'	0°03' 0°11'

Rear

Cross Camber  
 Total Toe  
 Thrust Angle  
 Axle Offset

Actual	Before	Specified Range
0°01'	-0°47'	
0°09'	-0°26'	0°05' 0°21'
0°01'	-0°12'	
0mm	0mm	